

# Material Safety Data Sheet



PO Box 531  
Derby, KS 67037  
1-316-640-7149

[www.flame-block.com](http://www.flame-block.com)

[info@flame-block.com](mailto:info@flame-block.com)

---

## Section 1 – Product and Company Information

Product Name: Flame Stop I, I-C, I-DS, II, III, and IV  
Hazard Rating: Health: 1, Fire:0, Reactivity: 0, PPI: 0

Company Identification: Flame Stop, Inc.  
924 Blue Mound Rd.  
Forth Worth, TX 76131

Phone: 1-877-397-7867  
Chemtrec (24 hr.) 1-800-424-9300

Product Class: Proprietary  
Shipping Name: Flame Stop I, I-C, I-DS, II, III, and IV

---

## Section II – Ingredient and Hazard Information

Proprietary Non Hazardous Chemicals

---

## Section III – Physical Data

Form: Liquid  
Appearance/Color: Clear, Flame Stop II is white  
pH Value: 4.5-6.5  
Boiling Range: 212F  
Evaporation Rate: Slower than n-Butyl Acetate  
Vapor Density: Heavier than air  
% Volatile Weight: N/A  
% Volatile Volume: N/A  
Specific Gravity: proprietary

---

## Section IV – Fire and Explosion Hazard Data

Flammability Class: III B  
Flash Point: N/A  
Extinguishing Media: CO2, Foam, Dry Chemical, Water  
Special Firefighting Procedures: Use self contained breathing apparatus  
Unusual Fire and Explosion Hazards: None

---

## Section V – Health Hazard Data

Effects of Over Exposure: Eye irritation, nausea,  
Prolonged exposure may cause drying of skin  
Permissible Exposure Level: Undetermined

### First Aid:

Inhalation: Remove from exposure  
Eye Contact: Flush with water for 15 minutes  
Skin Contact: Wash with soap and water  
Possible routes of entry: Inhalation, Ingestion, Skin Absorption

---

## Section VI – Stability and Reactivity

Stability: Yes  
Hazardous Polymerization: Will not occur  
Incompatibility: Avoid water-reactive agents  
Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide

---

## Section VII – Spill or Leak Procedures

Steps to be taken in case material is released or spilled  
Remove spills with inert absorbent  
Waste Disposal Method: Dispose of in accordance with Federal, State, and Local  
Regulations

---

## Section VIII – Exposure Controls/Personal protection

Occupational Exposure Limits:  
ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL  
Respiratory Protection: If in direct contact or spray application, use a dust or paint mask.  
Ventilation: Required only when applying in a confined area  
Eye Protection: Wear safety glasses or goggles to guard against splashes  
Protective gloves: not required unless direct contact

Disclaimer: The data herein is believed to be correct. However, since conditions of use are outside our control, it does not represent a warranty or representation for which Flame Stop, Inc. assumes any legal responsibility. Flame Stop makes no guarantee or warranty since they have no control over application conditions.