

Material Safety Data Sheet



PO Box 531
Derby, KS 67037
1-316-640-7149

www.flame-block.com

info@flame-block.com

Section 1 – Product and Company Information

Product Name: Flame Stop Intumescent Paint
Hazard Rating: Health: 1, Fire:0, Reactivity: 0

Company Identification: Flame Stop, Inc.
924 Blue Mound Rd.
Forth Worth, TX 76131

Phone: 1-877-397-7867
Chemtrec (24 hr.) 1-800-424-9300

Product Class: Proprietary
Shipping Name: Flame Stop Intumescent Paint

Section II – Ingredient and Hazard Information

Proprietary Non Hazardous Chemicals

Section III – Physical Data

Form: Liquid
Appearance/Color: white
pH Value: 6-8.5
Boiling Range: 212F
Evaporation Rate: Slower than n-Butyl Acetate
Vapor Density: Heavier than air
% Volatile Weight: N/A
% Volatile Volume: N/A
Specific Gravity: proprietary

Section IV – Fire and Explosion Hazard Data

Flammability Class: III B
Flash Point: N/A
Extinguishing Media: CO2, Foam, Dry Chemical, Water
Special Firefighting Procedures: Use self contained breathing apparatus
Unusual Fire and Explosion Hazards: None

Section V – Health Hazard Data

Effects of Over Exposure: Eye irritation, nausea,
Prolonged exposure may cause drying of skin
Permissible Exposure Level: Undetermined

First Aid:

Inhalation: Remove from exposure
Eye Contact: Flush with water for 15 minutes
Skin Contact: Wash with soap and water
Possible routes of entry: Inhalation, Ingestion, Skin Absorption

Section VI – Stability and Reactivity

Stability: Yes
Hazardous Polymerization: Will not occur
Incompatibility: Avoid water-reactive agents
Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide

Section VII – Spill or Leak Procedures

Steps to be taken in case material is released or spilled
Remove spills with inert absorbent
Waste Disposal Method: Dispose of in accordance with Federal, State, and Local
Regulations

Section VIII – Exposure Controls/Personal protection

Occupational Exposure Limits:
ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL
Respiratory Protection: If in direct contact or spray application, use a dust or paint mask.
Ventilation: Required only when applying in a confined area
Eye Protection: Wear safety glasses or goggles to guard against splashes
Protective gloves: not required unless direct contact

Disclaimer: The data herein is believed to be correct. However, since conditions of use are outside our control, it does not represent a warranty or representation for which Flame Stop, Inc. assumes any legal responsibility. Flame Stop makes no guarantee or warranty since they have no control over application conditions.